



King Long XMQ6520 – Mini Bus 15 seats (diesel)





Specification		
Dimensions	Overall length (mm): 5200	
	Overall width (mm): 1700	
	Overall height (mm): 1980	
	Wheel base (mm): 2590	
	Minimum ground clearance (mm): 260	
Speed	Maximum speed : 120 km/h	
Engine	YC4F90-23, Euro II, Displacement : 2.488 L Rated power/speed (kw/rpm) : 65/3400 Maximum Torque/speed (N.m/rpm) : 210/2000-2400	
Transmission	5-speed mechanically controlled	
Clutch	Single : Hydraulic pressure operated	
Suspension	Front : Torsion bar spring – Rear : Leaf spring	
Brakes	Front disc and Rear drums	
Lamp	Front fog lamp – High mount stop lamp	
Tires and Wheels	195/70R15 brand Vaccum Steel rim	
Steering	Power steering	
Passenger Capacity	Driver seat : Adjustable dump driver seat with leather cover and safety belt Passenger seat : 15 seats	


Air Conditioner	Front and rear AC
Appearance	White flat paint
	All-in-one drill crystal lamp
	Manual rear-view mirrors
	White glass window
	Common rear combined lamp
Interior trimming and other specification	Driver side sun visor
	Floor PVC
	Manual front window
	Flocking ceiling
	Seat belt in all row
	SA-03 seats
	Radio

Options not included (paying)	Center control door lock
	High roof body
Remark	 King Long reserves the right to change the spec without previous notice; The price is based on the warranty period of two (2) year or 60,000km, whichever first.
Delivery time	50 days at LC's reception 45-50 days shipping transit











Others configurations



XMQ 6520 15 seats



Ambulance



Cargo



Police